


## Wildcat Category 6 Outdoor F/UTP Ethernet Cable

SKU: C6-UV

- Industrial grade WISP cable
- Tough, Thick Black UV-Stable Outer Jacket
- 1000BASE-T Certified Category 6
- Level-1 F/UTP Foil Shielded Twisted Pair
- Anti-Crosstalk Divider
- ESD drain for outdoor installations
- Reduced EMI crosstalk and improved SNR



Mechanical Specifications	
Standards	YD/T 1019-2013, TIA-568-C.2
Cable Specifications	4x2x0.56mm
Conductor Material	BC
Conductor Diameter	0.56mm (±0.005mm)
Insulation Material	HDPE
Insulation Diameter	1.00mm (±0.03mm)
Shielding Material	ALP
Drain Wire Material	CCA
Drain Wire Diameter	0.5mm
Jacket Material	PE
Jacket Surface	Smooth, Clean, Shiny
Jacket Colour	Black
Jacket Thickness	0.55mm (±0.05mm)
Jacket Diameter	6.3mm (±0.4mm)



## Electrical Specifications

Minimum Single Bending Radius	51mm
1.0-100.0MHz Characteristic Impedance	100±15
1.0-100.0MHz Delay Difference (20°C)	<45ns/100m
DC Resistance (20°C)	7.00
Operating Temperature Range	-20°C to +60°C