

SPECIFICATION SHEET

Telco DAS MiMo Omnidirectional Ceiling Antenna - 700-2700MHz

SKU: DAS-7-38-CM-N

- Wideband Frequency Support 2G, 3G & 4G
- MiMo Design
- High Gain
- RoHS Compliant
- High quality ABS construction

Electrical Specifications



Frequency Range	698-960MHz / 1710-2700MHz
Polarization	Vertical
Gain	4dBi / 5dBi
VSWR	≤1.8:1
Horizontal Beamwidth	85° / 55°
Input Impedance	50 Ω
Max Power	50 W

Mechanical Specifications

Construction Material	ABS Plastic
Connector Type	2 x N Female
Dimensions	208 x 55mm (ø x H)
Weight	800g
Operating Temperature	-30°C +°45C
Colour	White


Telco Antennas Pty Ltd

WWW.TELCOANTENNAS.COM.AU

 | VHF | UHF | 3G | 4G | 5G | IoT | WiFi | ISM | Microwave | WiFi |
 Remote & High Speed Communications Design & Integration | Electrical & Data Contracting |

sales@telcoantennas.com.au + 61 7 3393 9919





Installation Guide:

- 1. Drill a 33-35mm ø Hole in the Ceiling
- 2. Connect the N Female Connectors to the N Males on the end of the Cable/Adaptors.
- 3. Install the Antenna as shown in the picture above and tighten the nuts.

Telco Antennas Pty Ltd

sales@telcoantennas.com.au + 61 7 3393 9919