



# TAOGLAS®



## Datasheet

### 5G/4G Terminal Mount Monopole Antenna

**Part No:**  
TG.55.8113

**Description:**

5G/4G Terminal Mount Monopole Antenna with 90° Hinged SMA (M)

**Features:**

- Covering Sub 6GHz 5G NR Bands
- Covering Worldwide 4G Bands
- 600MHz-6GHz Bandwidth
- High Efficiency up to 80%
- 3G/2G Fallback with NB-IoT and CAT-M capabilities
- 90° Hinged Right Angle SMA (M) Connector
- Straight Dimensions: 172 x 23.9 x 13 mm
- Right Angle Dimensions: 148 x 42.4 x 13 mm
- RoHS & REACH Compliant

|                            |    |
|----------------------------|----|
| 1. Introduction            | 3  |
| 2. Specifications          | 4  |
| 3. Antenna Characteristics | 7  |
| 4. Radiation Patterns      | 9  |
| 5. Mechanical Drawing      | 75 |
| 6. Packaging               | 76 |
| 7. Application Note        | 77 |
| <hr/>                      |    |
| Changelog                  | 79 |

Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly prohibited.



# 1. Introduction



The Taoglas TG.55.8113 is a 5G/4G monopole antenna, designed primarily for use with modules and devices that require high efficiency and peak gain. It delivers best in class throughput on all major cellular bands worldwide, perfect for access points, terminals, and routers. The TG.55 covers many 5G NR Sub 6GHz bands including the new Extended LTE Band 71. It has an SMA (M) connector as standard and is an ideal solution for any device requiring reliable performance in a slim form factor.

Typical Applications include:

- Gateways & Routers
- Smart Metering
- Vending Machines
- Industrial IoT
- Smart Home
- Connected Enterprise

The TG.55 exhibits an efficiency of up to 80% across wideband 5G/4G bands and is backward compatible with 3G/2G cellular applications. The TG.55 is a fully omnidirectional antenna as seen in the radiation patterns and is stable across all bands. The SMA (M) connector hinge mechanism allows the antenna to be rotated into the preferred orientation which helps to avoid other antennas or objects. This also helps with isolation by pointing the antennas in different directions when used in MIMO systems or when other antennas are present on the same device. The antenna blade can swivel 90 degrees from the connector accommodating different installation configurations.

The TG.55.8113 is also available with a white enclosure – TG.55.8113W. The connector can also be customized based on an MOQ.

Contact your regional Taoglas customer support team to request these services or additional support to integrate and test this antenna’s performance in your device.

## 2. Specifications

| Electrical                      |                  |             |               |                       |               |               |               |               |                       |               |
|---------------------------------|------------------|-------------|---------------|-----------------------|---------------|---------------|---------------|---------------|-----------------------|---------------|
| Frequency (MHz)                 | 5G NR<br>Band 71 | LTE<br>700  | GSM<br>850/90 | 5G NR B<br>74, 75, 76 | GPS<br>L1     | DCS           | UMTS1         | LTE<br>2600   | 5G NR B<br>77, 78, 79 | LTE<br>5200   |
|                                 | 617<br>~698      | 698<br>~824 | 824<br>~960   | 1427<br>~1518         | 1563<br>~1587 | 1710<br>~1880 | 1920<br>~2170 | 2300<br>~2690 | 3300<br>~5000         | 5150<br>~5925 |
| Efficiency (%)                  |                  |             |               |                       |               |               |               |               |                       |               |
| Free space straight             | 35.93            | 25.92       | 38.33         | 38.08                 | 46.37         | 69.80         | 59.03         | 44.92         | 50.45                 | 45.96         |
| Free space bent                 | 43.77            | 30.56       | 51.77         | 44.23                 | 53.07         | 78.02         | 65.02         | 51.53         | 48.91                 | 34.98         |
| On 30x30 cm GND edge straight   | 44.39            | 39.43       | 59.39         | 49.21                 | 57.94         | 66.24         | 52.47         | 42.63         | 24.71                 | 21.90         |
| On 30x30 cm GND edge bent       | 42.05            | 30.02       | 52.28         | 46.78                 | 48.79         | 68.89         | 54.17         | 39.78         | 21.31                 | 22.53         |
| On 30x30 cm GND centre straight | 9.12             | 7.30        | 21.46         | 38.09                 | 51.59         | 65.46         | 48.14         | 42.25         | 36.68                 | 24.48         |
| On 30x30 cm GND centre bent     | 4.88             | 10.77       | 34.32         | 36.52                 | 46.16         | 60.36         | 47.55         | 42.15         | 36.82                 | 21.93         |
| Straight on 9x15cm Ground plane | 29.0             | 53.4        | 81.1          | 62.3                  | 61.1          | 69.80         | 80.1          | 61.6          | 64.2                  | 58.6          |
| Bent on 9x15cm Ground plane     | 24.0             | 47.4        | 82.2          | 52.0                  | 53            | 78.02         | 84.2          | 68.4          | 71.9                  | 64.3          |
| Average Gain (dB)               |                  |             |               |                       |               |               |               |               |                       |               |
| Free space straight             | -4.45            | -5.86       | -4.16         | -4.19                 | -3.34         | -1.56         | -2.29         | -3.48         | -2.97                 | -3.38         |
| Free space bent                 | -3.59            | -5.15       | -2.86         | -3.54                 | -2.75         | -1.08         | -1.87         | -2.88         | -3.11                 | -4.56         |
| On 30x30 cm GND edge straight   | -3.53            | -4.04       | -2.26         | -3.08                 | -2.37         | -1.79         | -2.80         | -3.70         | -6.07                 | -6.60         |
| On 30x30 cm GND edge bent       | -3.76            | -5.23       | -2.82         | -3.30                 | -3.12         | -1.62         | -2.66         | -4.00         | -6.71                 | -6.47         |
| On 30x30 cm GND centre straight | -10.40           | -11.37      | -6.68         | -4.19                 | -2.87         | -1.84         | -3.17         | -3.74         | -4.36                 | -6.11         |
| On 30x30 cm GND centre bent     | -13.12           | -9.68       | -4.64         | -4.37                 | -3.36         | -2.19         | -3.23         | -3.75         | -4.34                 | -6.59         |
| Straight on 9x15cm Ground plane | -5.38            | -2.73       | -0.91         | -2.06                 | -2.87         | -1.84         | -0.97         | -2.10         | -1.9                  | -2.32         |
| Bent on 9x15cm Ground plane     | -6.20            | -3.24       | -0.85         | -2.84                 | -3.36         | -2.19         | -0.75         | -1.65         | -1.4                  | -1.92         |
| Peak Gain (dBi)                 |                  |             |               |                       |               |               |               |               |                       |               |
| Free space straight             | -0.68            | -2.14       | 0.15          | -0.74                 | -0.59         | 1.37          | 0.93          | 0.73          | 1.51                  | 1.73          |
| Free space bent                 | 0.14             | -1.88       | 0.58          | 0.87                  | 1.98          | 3.09          | 2.45          | 1.69          | 1.50                  | 0.70          |
| On 30x30 cm GND edge straight   | 0.94             | -0.32       | 2.56          | 1.00                  | 1.26          | 1.93          | 1.42          | 1.24          | -0.84                 | -1.48         |
| On 30x30 cm GND edge bent       | 0.63             | -1.99       | -0.02         | -0.59                 | 0.37          | 1.66          | 0.49          | 0.13          | 0.53                  | -0.25         |
| On 30x30 cm GND centre straight | -5.47            | -5.46       | 0.02          | 0.75                  | 2.30          | 3.44          | 2.48          | 2.36          | 4.66                  | 2.40          |
| On 30x30 cm GND centre bent     | -9.07            | -6.11       | -1.12         | 3.76                  | 4.99          | 6.10          | 4.84          | 3.46          | 3.92                  | 1.80          |
| Straight on 9x15cm Ground plane | -0.26            | 3.58        | 3.65          | 2.53                  | 1.26          | 1.93          | 4.18          | 3.79          | 7.3                   | 5.43          |
| Bent on 9x15cm Ground plane     | -1.69            | 2.52        | 3.86          | 2.01                  | 0.37          | 1.66          | 4.49          | 5.03          | 4.9                   | 6.29          |
| <b>Impedance</b>                | 50Ω              |             |               |                       |               |               |               |               |                       |               |
| <b>Polarization</b>             | Linear           |             |               |                       |               |               |               |               |                       |               |
| <b>Radiation Pattern</b>        | Omni             |             |               |                       |               |               |               |               |                       |               |
| <b>Max. input power</b>         | 2W               |             |               |                       |               |               |               |               |                       |               |





| <b>Mechanical</b>             |                            |
|-------------------------------|----------------------------|
| <b>SMA Connector Diameter</b> | 13mm                       |
| <b>Planner Dimension</b>      | 172mm * 23.88mm            |
| <b>Casing</b>                 | ABS + PC                   |
| <b>Connector</b>              | SMA (M)                    |
| <b>Weight</b>                 | 24.3g                      |
| <b>Environmental</b>          |                            |
| <b>Temperature Range</b>      | -40°C to 85°C              |
| <b>Humidity</b>               | Non-condensing 65°C 95% RH |



| 5G/4G Bands |   |                      |                 |                     |                       |                           |                         |                             |
|-------------|---|----------------------|-----------------|---------------------|-----------------------|---------------------------|-------------------------|-----------------------------|
| Band Number | 5GNR / FR1 / LTE / LTE-Advanced / WCDMA / HSPA / HSPA+ / TD-SCDMA |                      |                 |                     |                       |                           |                         |                             |
|             | Uplink  | Downlink             | Free space Bent | Free space Straight | 30x30cm GND edge bent | 30x30cm GND edge straight | 30x30cm GND centre bent | 30x30cm GND centre straight |
| 1           | UL: 1920 to 1980  | DL: 2110 to 2170     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 2           | UL: 1850 to 1910  | DL: 1930 to 1990     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 3           | UL: 1710 to 1785  | DL: 1805 to 1880     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 4           | UL: 1710 to 1755  | DL: 2110 to 2155     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 5           | UL: 824 to 849  | DL: 869 to 894       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 7           | UL: 2500 to 2570  | DL: 2620 to 2690     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 8           | UL: 880 to 915  | DL: 925 to 960       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 9           | UL: 1749.9 to 1784.9  | DL: 1844.9 to 1879.9 | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 11          | UL: 1427.9 to 1447.9  | DL: 1475.9 to 1495.9 | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 12          | UL: 699 to 716  | DL: 729 to 746       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 13          | UL: 777 to 787  | DL: 746 to 756       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 14          | UL: 788 to 798  | DL: 758 to 768       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 17          | UL: 704 to 716  | DL: 734 to 746       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 18          | UL: 815 to 830  | DL: 860 to 875       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 19          | UL: 830 to 845  | DL: 875 to 890       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 20          | UL: 832 to 862  | DL: 791 to 821       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 21          | UL: 1447.9 to 1462.9  | DL: 1495.9 to 1510.9 | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 22          | UL: 3410 to 3490  | DL: 3510 to 3590     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 23          | UL: 2000 to 2020  | DL: 2180 to 2200     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 24          | UL: 1625.5 to 1660.5  | DL: 1525 to 1559     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 25          | UL: 1850 to 1915  | DL: 1930 to 1995     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 26          | UL: 814 to 849  | DL: 859 to 894       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 27          | UL: 807 to 824  | DL: 852 to 869       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 28          | UL: 703 to 748  | DL: 758 to 803       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 29          | UL: -   | DL: 717 to 728       | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 30          | UL: 2305 to 2315  | DL: 2350 to 2360     | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 31          | UL: 452.5 to 457.5  | DL: 462.5 to 467.5   | ✗               | ✗                   | ✗                     | ✗                         | ✗                       | ✗                           |
| 32          | UL: -   | DL: 1452 – 1496      | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 35          |   | 1850 to 1910         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 38          |   | 2570 to 2620         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 39          |   | 1880 to 1920         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 40          |   | 2300 to 2400         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 41          |   | 2496 to 2690         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 42          |   | 3400 to 3600         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 43          |   | 3600 to 3800         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 48          |   | 3550 to 3700         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 66          | UL: 1710-1780   | DL: 2110-2200        | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 71          |   | 617 to 698           | ✓               | ✓                   | ✓                     | ✓                         | ✗                       | ✗                           |
| 74/75/76    |   | 1427 to 1518         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 77          |   | 3300 to 4200         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 78          |   | 3300 to 3800         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |
| 79          |   | 4400 to 5000         | ✓               | ✓                   | ✓                     | ✓                         | ✓                       | ✓                           |

### 3. Antenna Characteristics


#### 3.1 Return Loss




### 3.2 Efficiency





### 3.3 Average Gain



TG.55.8113



### 3.4 Peak Gain





## 4. Radiation Patterns


### 4.1 Test Setup




Straight Free Space

## 4.2 Straight 2D & 3D Radiation Patterns


652MHz




XY Plane





XZ Plane





YZ Plane





751MHz




890MHz




1470MHz




1805MHz




XY Plane



XZ Plane





YZ Plane








1920MHz




1990MHz




2595MHz




XY Plane




XZ Plane




YZ Plane




3550MHz




XY Plane





XZ Plane




YZ Plane



5530MHz



4.3 Test Setup





Bent Free Space




4.4 Bent Free Space 2D & 3D Radiation Patterns


652MHz




751MHz




XY Plane





XZ Plane





YZ Plane





890MHz




1470MHz






1805MHz



1920MHz





XY Plane      XZ Plane      YZ Plane







1990MHz




2595MHz




XY Plane





XZ Plane





YZ Plane




3550MHz



5530MHz





## 4.5 Test Setup




Straight 30x30cm Ground Plane Edge

## 4.6 Straight 30x30cm Ground Plane Edge 2D & 3D Radiation Patterns




652MHz



751MHz




XY Plane      XZ Plane      YZ Plane










890MHz




XY Plane      XZ Plane      YZ Plane




1470MHz




1805MHz




XY Plane





XZ Plane





YZ Plane





1920MHz





1990MHz



2595MHz





3550MHz





5530MHz





4.7 Test Setup





Bent 30x30cm Ground Plane Edge

4.8 Bent 30x30cm Ground Plane Edge 2D & 3D Radiation Patterns



652MHz





751MHz




890MHz




1470MHz




1805MHz




XY Plane



XZ Plane





YZ Plane









1920MHz




1990MHz




2595MHz




3550MHz




XY Plane




XZ Plane




YZ Plane




5530MHz




XY Plane




XZ Plane



YZ Plane





4.9 Test Setup



Straight 30x30cm Ground Plane Centre



4.10 Straight 30x30cm Ground Plane Centre 2D & 3D Radiation Patterns

652MHz









751MHz




890MHz




1470MHz




1805MHz




XY Plane




XZ Plane






YZ Plane




1920MHz






XY Plane      XZ Plane      YZ Plane





1990MHz



XY Plane      XZ Plane      YZ Plane





2595MHz








3550MHz



5530MHz




4.11 Test Setup




Bent 30x30cm Ground Plane Centre

## 4.12 Bent 30x30cm Ground Plane Centre 2D & 3D Radiation Patterns


652MHz




XY Plane





XZ Plane





YZ Plane





751MHz



890MHz




1470MHz










1805MHz





XY Plane      XZ Plane      YZ Plane





1920MHz





1990MHz





2595MHz




3550MHz



5530MHz




# 5. Mechanical Drawing (Units: mm)






## 6. Packaging


1pc TG.55.8113 per Small PE Bag  
 Dimensions: 30\*210mm  
 Weight: 31g




20pcs per Large PE Bag  
 Dimensions: 180\*265mm  
 Weight: 620g



400pcs TG.55.8113 per Carton  
 Carton Dimensions: 320\*250\*230mm  
 Weight: 13Kg




Pallet Dimensions:  
 1200\*1000\*1350mm  
 60 Cartons per Pallet  
 12 Cartons per layer, 5 Layers




## 7. Application Note


### 3.1 Return Loss




### 3.2 Efficiency



### 3.3 Average Gain



### 3.4 Peak Gain



Changelog for the datasheet

**SPE-19-8-061 – TG.55.8113**

| <b>Revision: E (Current Version)</b> |                |
|--------------------------------------|----------------|
| Date:                                | 2022-07-05     |
| Changes:                             | Updatd drawing |
| Changes Made by:                     | Jack Conroy    |

**Previous Revisions**

| <b>Revision: D</b> |                 |
|--------------------|-----------------|
| Date:              | 2020-11-10      |
| Changes:           | Updated drawing |
| Changes Made by:   | Jack Conroy     |

| <b>Revision: C</b> |   |
|--------------------|---|
| Date:              | 2019-10-16                                |
| Changes:           | Updated data to include new ground planes |
| Changes Made by:   | Jack Conroy                               |

| <b>Revision: B</b> |                     |
|--------------------|---------------------|
| Date:              | 2019-08-29          |
| Changes:           | Updated description |
| Changes Made by:   | David Connolly      |

| <b>Revision: A (Initial Launch)</b> |                               |
|-------------------------------------|-------------------------------|
| Date:                               | 2019-05-22                    |
| Changes:                            | Initial Specification Release |
| Changes Made by:                    | Jack Conroy                   |

